

USAGE FOR CHESSPIT EMTIERS, FOR CLEANING COMBINATION MACHINES

GENERAL DEFINITIONS




- ➤ 27485 lb-ft vertical Split Shaft PTO is designed for Heavy Duty trucks with 3 stages.
- > The gearbox can be installed as horizontal if needed.
- ➤ It can provide 100% of input speed.
- Control system can be pneumatic or mechanic.
- > PTO shaft can be at differential side or cabin side.
- > Second PTO output is an option.
- In case of double PTO output is requested. Pto outputs can be shifted independently.
- > PTO outputs can be design with all ISO standard flanges as well as suitable housing for any kind of hydraulic pump.
- Cooling system can be mount on the gearbox.
- > Engage/Disengage Sensor can be installed to observe, if PTO is engaged or not, also
- > RPM Counter is another option.


10.03.2018


Product Code Date Sheet No

USAGE FOR CHESSPIT EMTIERS, FOR CLEANING **COMBINATION MACHINES**

PTO OUTPUT DEFINITIONS







(1)	Input Side
(2)	Output Side
3	PTO Output
(A)	Air Inlet (Engage)
(B)	Air Inlet (Disengage)

Kozmaksan has all rights to change information in this catalogue without announcing it. This document is representing general information. It is not a contract. All information belongs to only PTO/Split Shaft. Do not use PTO/Split Shaft, if it is not suitable for your engine and main transmission.

Pumps, shafts and other parts should not be longer or heavier then approved distance and weight by the manufacturer of main transmission and engine.

10.03.2018


Website: www.kozmaksan.net

USAGE FOR CHESSPIT EMTIERS, FOR CLEANING **COMBINATION MACHINES**

TECHNICAL INFORMATION

TECHNICAL VALUES					
	MAX. VALUES	INTERNAL RATIO	MAX. RPM		
҈ ♦ ♦	3800 kgm	1/1	-		
3>	350 kW	1/1.3 - 1/1.7	2500 rpm-3500 rpm		

WEIGHT	_250 kg
BODY MATERIAL	GH190
KIND OF OIL QUANTITY	80W90 15 lt



Kozmaksan has all rights to change information in this catalogue without announcing it. This document is representing general information. It is not a contract.
 All information belongs to only PTO/Split Shaft. Do not use PTO/Split Shaft, if it is not suitable for your engine and main transmission.
 Pumps, shafts and other parts should not be longer or heavier then approved distance and weight by the manufacturer of main transmission and engine.